

WHITE LINED CHIPBOARD

Basis-Qualitäten Hoya Karton

Headline Grades Hoya Karton

 Smurfit Kappa Hoya Paper & Board GmbH
 Von-dem-Bussche-Str. 1, D-27318 Hoya

Telefon + 49 (0) 4251 814-0

E-Mail: info.hoya@smurfitkappa.de

BEZEICHNUNG / NAME		QUALITÄT / QUALITY	RÜCKSEITE / REVERSE	GRAMMATUR / GRAMMAGE
(HB) HANSABOARD				
X	Hansaboard	GD 2	grau / grey	300 - 550 g/m ²
	Hansaboard Cobb	GD 2	grau / grey	300 - 550 g/m ²
EUROBOARD SPEZIAL WEISS (ESW) / EUROBOARD SPECIAL WHITE (ESW)				
X	ESW	GT 2	hell / bright	300 - 500 g/m ²
	ESW Cobb	GT 2	hell / bright	300 - 500 g/m ²
	ESW + MB12 / adsorption technology	GT 2	hell / bright	300 - 500 g/m ²
X	ESW Grease Guard FOOD	GT 2	hell / bright	300 - 500 g/m ²
	ESW Grease Guard FOOD, fully sized	GT 2	hell / bright	300 - 500 g/m ²
	ESW Grease Guard FOOD + MB12 / barrier coating + adsorption tech.	GT 2	hell / bright	300 - 500 g/m ²
	ESW Grease Guard FOOD, fully sized, black	GT 2	hell / bright	300 - 500 g/m ²
	ESW Grease Guard FOOD, fully sized, black + MB12 / barrier coating + adsorption tech.	GT 2	hell / bright	300 - 500 g/m ²
X	ESW Grease Guard HIGH	GT 2	hell / bright	300 - 500 g/m ²
	ESW Grease Guard HIGH + MB12 / barrier coating + adsorption tech.	GT 2	hell / bright	300 - 500 g/m ²
TWIN COAT				
X	Twin Coat	GT 1	weiß / white	320 - 550 g/m ²
	Twin Coat + MB12 / adsorption technology	GT 1	weiß / white	320 - 550 g/m ²
EUROBOARD SPEZIAL KRAFT (ESK) / EUROBOARD SPECIAL KRAFT (ESK)				
X	ESK	GT 4	braun / brown	300 - 550 g/m ²
	ESK, fully sized	GT 4	braun / brown	300 - 550 g/m ²

X = in Mustermappe enthalten / in samples folder included

WHITE LINED CHIPBOARD

Technische Daten
Technical Data

Smurfit Kappa Hoya Paper & Board
 Von-dem-Bussche-Str. 1, D-27318 Hoya
 Telefon + 49 (0) 4251 814-0
 E-Mail: info.hoya@smurfitkappa.de

Papiermaschine 4 <i>board machine 4</i>	
Jahreskapazität / <i>annual capacity</i>	85.000 to
Arbeitsbreite / <i>machinery width</i>	2.280 mm
Formatware / <i>sheets</i>	300 x 600 - 1.600 x 1.600 mm — 300 - 550 g/m ²
Rollenware / <i>reels</i>	min. 300 mm Breite / <i>wide reels</i> — 300 - 550 g/m ²

Auf Wunsch :

- Schwarze Rückseite
- Twin Coat (beidseitig gestrichen)
- Grease Guard (Fettbarriere)
- MB12 Migrationsbarriere

On request:

- Reverse black
- Twin Coat (2 sides coated)
- Grease Guard (greaseproof barrier)
- MB12 (migration barrier)

Gut zu wissen:

**Wir sind zertifiziert nach DIN EN ISO 9001,
 DIN EN ISO 14001, DIN ISO 50001, EN 15593 und FSC**

Good to know:

*We are certified according to DIN EN ISO 9001,
 DIN EN ISO 14001, DIN ISO 50001, EN 15593 und FSC*

